

03nov04 13:16:55 User015070 Session D10524.1  
Sub account: HARD1.006A-CSP

FILE HARDFOR2.DOC

\*\*\*ENGLISH ABSTRACTS OF FOREIGN PATENTS\*\*\*

File 351:Derwent WPI 1963-2004/UD,UM &UP=200470

(c) 2004 Thomson Derwent

\*File 351: For more current information, include File 331 in your search.  
Enter HELP NEWS 331 for details.

Set Items Description

?.exs td692

11/7/1

DIALOG(R)File 351:Derwent WPI

(c) 2004 Thomson Derwent. All rts. reserv.

007709587

WPI Acc No: 1988-343519/\*198848\*

Cement moulding for flooring verandas and balconies - comprises inorganic  
lightweight aggregate upper layer and lower layer contg. reinforcing  
fibre, pulp and fibrous mesh

Patent Assignee: SEKISUI CHEM IND CO LTD (SEKI )

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 63257631	A	19881025	JP 8794190	A	19870416	198848 B

Priority Applications (No Type Date): JP 8794190 A 19870416

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
JP 63257631	A	8		

Abstract (Basic): JP 63257631 A

A cement moulding comprises an upper layer contg. an inorganic  
light wt. aggregate, and a lower layer contg. a reinforcing fibre and  
pulp. In the lower layer, a fibrous mesh material is provided.

Pref. the cement moulding is obtd. by dehydration press moulding  
using a metallic mould provided with water-discharge pores at the  
moulding face. The inorganic light wt aggregate is Japanese shirasu,  
Japanese Kokaseki, obsidian, or perlite. The reinforcing fibre has a  
tensile modulus of elasticity of at least 3000 kg/sq.mm. The  
reinforcing fibre is aramid fibre, vinylon fibre or carbon fibre. The  
pulp is reproduced pulp and/or used paper pulp. The fibrous mesh  
material has a tensile modulus of elasticity of at least 3000 kg/sq.mm;  
and is aramid fibre, vinylon fibre or carbon fibre.

USE/ADVANTAGE - The cement moulding has superior light wt. and  
high impact resistance. The moulding is harmless to human bodies.

Derwent Class: A93; L02; P73

International Patent Class (Additional): B32B-013/00